

MAR 30 1999

ANALYTICAL REPORT

Mr. Richard Tyler
MILBANK MANUFACTURING INC
1400 E. Havens Street
Kokomo, IN 56901-3188

03/24/1999

Job Number: 99.01372
Page 1 of 3

Enclosed are the Analytical Results for the following samples submitted to TestAmerica, Inc. Indianapolis Division for analysis:

Project Description: 2X MONTHLY SAMPLING

Sample Number	Sample Description	Date Taken	Date Received
233628	2X MONTHLY GRAB	03/16/1999	03/17/1999
233629	2X MONTHLY COMP	03/16/1999	03/17/1999

TestAmerica, Inc. certifies that the analytical results contained herein apply only to the specific samples analyzed.

Reproduction of this analytical report is permitted only in its entirety.


Project Representative

ANALYTICAL REPORT

Mr. Richard Tyler
MILBANK MANUFACTURING INC
1400 E. Havens Street
Kokomo, IN 56901-3188

03/24/1999

Job No.: 99.01372

Page 2 of 3

Date Received: 03/17/1999

Job Description: 2X MONTHLY SAMPLING

Sample Number / Sample I.D.			Sample Date/	Analyst &		Reporting
Parameters	Result	Flag	Units	Date Analyzed	Method	Limit
233628	2X MONTHLY GRAB		03/16/1999			
Oil & Grease	<5.		mg/L	ceg / 03/23/1999	EPA 1664	<5.
233629	2X MONTHLY COMP		03/16/1999			
CBOD - Five Day	140		mg/L	tpd / 03/23/1999	EPA 405.1	<5.
CBOD - Five Day (PREP)	Complete			tpd / 03/18/1999	EPA 405.1	Complete
COD	400	d1x5	mg/L	ddm / 03/23/1999	EPA 410.4	<10.
Solids, Suspended	55		mg/L	cls / 03/22/1999	EPA 160.2	<5.
Zinc, ICP	1.4		mg/L	psc / 03/20/1999	EPA 200.7	<0.020

MAR 30 1999

FIELD REPORT

JOB #: 99.01372
CLIENT: MILBANK MFG.
PROJECT: 2x MONTHLY WASTEWATER SAMPLING
DATE: 3/16/99
SAMPLER(S): MTM

An ISCO model 6700 auto sampler was used in the sequential mode of operation. The sampler was equipped with plastic containers, tygon suction line, power pack, and strainer.

All reusable equipment is decontaminated withalconox, tap water, 5% nitric acid, and deionized water. New tygon suction tubing was used for the sampler. A stainless steel strainer was also used for the sampling event.

The sampler was set to take a sample every 30 minutes for 8 hours.

Monitoring start 7:30 on 3/16/99
Monitoring end 15:30 on 3/16/99

The samples were then composited based on flow weight, and preserved in the appropriate containers.

KEY TO ABBREVIATIONS

<	Less than; when appearing in the results column indicates the analyte was not detected at or above the reported value.
mg/L	Concentration in units of milligrams of analyte per Liter of sample. Measurement used for aqueous samples. Can also be expressed as parts per million (ppm).
ug/L	Concentration in units of micrograms of analyte per Liter of sample. Measurement used for aqueous samples. Can also be expressed as parts per billion (ppb).
mg/kg	Concentration in units of milligrams of analyte per kilogram of sample. Measurement used for non-aqueous samples. Can also be expressed as parts per million (ppm).
ug/kg	Concentration in units of micrograms of analyte per kilogram of sample. Measurement used for non-aqueous samples. Can also be expressed as parts per billion (ppb).
a	Indicates the sample concentration was quantitated using a diesel fuel standard.
b	Indicates the analyte of interest was also found in the method blank.
c	Samples resembles unknown Hydrocarbon.
d1	Indicates the analyte has elevated reporting limit due to high concentration.
d2	Indicates the analyte has elevated reporting limit due to matrix.
e	Indicates the reported concentration is estimated.
f	Indicates the sample concentration was quantitated using a fuel oil standard.
g	Indicates the sample concentration was quantitated using a gasoline standard.
h	Indicates the sample was analyzed past holding time.
i	Indicates the sample spike concentration was insufficient, due to high analyte concentration in the sample.
j	Indicates the reported concentration is below the Reporting Limit.
k	Indicates the sample concentration was quantitated using a kerosene standard.
l	Indicates an MS/MSD was not analyzed due to insufficient sample. An LCS duplicate has been provided.
m	Indicates the sample concentration was quantitated using a mineral spirits standard.
o	Indicates the sample concentration was quantitated using a motor oil standard.
p	Indicates the sample was post spiked due to sample matrix.
q	Indicates MS/MSD exceeded control limits. All other QCIs were in control.
r	Indicates the sample was received past holding time.
s	Indicates the sample concentration was quantitated using a stoddard solvent standard.
u	Indicates the sample was received improperly preserved and/or contained.
uj	Indicates the result is under the reporting limit and considered an estimated concentration.
TCLP	Indicates the Toxicity Characteristic Leaching Procedure was performed for this analysis.
ICP	Indicates the analysis was performed using Inductively Coupled Plasma Spectroscopy.
GFAA	Indicates the analysis was performed using Graphite Furnace Atomic Absorption Spectroscopy.
%	Percent; To convert ppm to %, divide the result by 10,000. To convert % to ppm, multiply the result by 10,000.
.	Reporting limits are elevated due to insufficient sample submitted by client.
Dry Weight	When indicated, the results are reported on a dry weight basis. The contribution of the moisture content in the sample is subtracted when calculating the concentration of the analyte.

3-16-99



Corporate Office:

P.O. Box 419028, Kansas City, Missouri 64141-0028 • (816) 483-5314 • FAX: 483-6357

TIME	READING
7:00	0061258.8
7:30	0061258.8
8:00	0061258.8
8:30	0061372.2
9:00	0061520.3
9:30	0061707.6
10:00	0061885.9
10:30	0062070.1
11:00	0062133.0
11:30	0062246.4
12:00	0062437.8
12:30	0062604.9
1:00	0062709.7
1:30	0062977.3
2:00	0063176.1
2:30	0063346.0
3:00	0063540.0
3:30	0063712.2
4:00	0063735.9

Manufacturer of Meter Mounting Equipment Since 1927
Kansas City, MO • El Dorado, AR • Concordia, MO • Kokomo, IN • Reno, NV

MIL0002961